

LWL
TR-74-71
c. 1

TECHNICAL REPORT NO. 74-71

AN IMPROVED ICY BALL REFRIGERATOR

by

Nicholas Montanarelli
Biological Science Branch

TECHNICAL LIBRARY
BLDG. 305
ABERDEEN PROVING GROUND, MD.
STEAP-TL

COUNTED IN

1974

Final Report

Contract No. DAAD05-73-C-0549

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

U. S. ARMY LAND WARFARE LABORATORY

Aberdeen Proving Ground, Maryland 21005

20081001 218

LWL
TR-74-71
c. 1

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER TECHNICAL REPORT NO. 74-71	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) AN IMPROVED ICY BALL REFRIGERATOR		5. TYPE OF REPORT & PERIOD COVERED Final Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Nicholas Montanarelli Biological Sciences Branch		8. CONTRACT OR GRANT NUMBER(s) Contract DAAD05-73-C-0549
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army Land Warfare Laboratory Aberdeen Proving Ground, MD 21005		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Task No. 02-B-73
11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE April 1974
		13. NUMBER OF PAGES 17
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES TECHNICAL LIBRARY BLDG. 305 ABERDEEN PROVING GROUND, MD. STEAP-TL		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Remote Area Refrigeration Heat Absorption Refrigerator System Refrigerated Box		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Two Icy Ball Refrigerator Units of improved designed compared with earlier units fabricated under this program were tested in the laboratory and in the field. Under both laboratory and hot-wet field conditions the units performed reliably. Adequate inside-the-box refrigeration temperatures were maintained in a 4 cu ft insulated storage box under hot-wet field conditions. The present units, however, did not maintain acceptable refrigeration temperatures under these conditions in an 8 cu ft box.		

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

PREFACE

The work described in this report was performed under USALWL Contract No. DAAD05-73-C-0549. With the completion of the reliability testing both units were sent to US Army Natick Labs, MA for military test and evaluation.

AD-782118

TABLE OF CONTENTS

	Page
REPORT DOCUMENTATION PAGE (DD FORM 1473)	iii
PREFACE	v
INTRODUCTION	3
PROCEDURES	4
Laboratory Tests	4
Field Tests	4
RESULTS	6
Laboratory Tests	6
Field Tests	6
DISCUSSION	12
CONCLUSION AND RECOMMENDATIONS	13
DISTRIBUTION LIST	14

INTRODUCTION

At the request of the US Army Land Warfare Laboratory, a test program to evaluate the continuous performance of the Icy Ball Refrigerator was performed under Contract No. DAAD05-73-C-0549, Amendment/Modification No. P00001.

This document presents a technical discussion concerning the ambient conditions in which the tests were performed, the cycle time, and system pressures. Test results are summarized and a final discussion of the results is presented along with some conclusions and recommendations that emerged from the test program.

PROCEDURES

Two Icy Ball Units (Unit 1 and Unit 2) were tested in 4 cu ft boxes insulated with 2-1/2 inches of 2-pound density polyurethane foam. Figure 1 shows the various components of the Icy Ball system, including the refrigeration unit, heating stove, cooling water tank and insulated box. The present Icy Ball Units each had an initial internal pressure of approximately 15 psig.

Laboratory Tests

For these tests, the insulated boxes were loaded with 4 containers, each holding 12.5 lb of water, placed uniformly at the bottom of the box. Temperature measurements were made in the center of each container of water. To perform the regeneration process, a Coleman stove and a cooling water tank with 22 gallons of water were used, identical to those supplied to the Government under an earlier contract.

Icy Ball system temperatures and pressures were recorded prior to, during and after regeneration. It was assumed that a five-minute period would be required to record the initial data, start the Coleman stove and place the Icy Ball Unit in the water tank. Pressure readings were taken every five minutes for the first twenty minutes and then at intervals of ten to fifteen minutes for the remaining portion of the 90-minute regeneration cycle. During the regeneration cycle, the pressure history was recorded. Continuous temperature recordings were made with a Honeywell/Brown circular chart recorder.

Field Tests

Two Icy Ball Refrigerator Units were tested in the Chiva-Chiva antenna farm area of the US Army Tropic Test Center, Panama Canal Zone. The tests were conducted with a 4 cu ft box and also with an 8 cu ft box. Meteorological data were taken during 16 days of continuous tests to provide a record of the prevailing ambient conditions.



Figure 1. Icy Ball Refrigerator System Showing Refrigeration Unit, Heating Stove, Cooling Water Tank And Insulated Box

RESULTS

Laboratory Tests

Averages of the daily temperatures maintained by each of the two Icy Ball Units tested in 4 cu ft boxes are shown in Table 1. The range of daily temperatures is also shown in this Table. It can be seen from Table 1 that the average daily temperatures, with the exception of Day 1 (2-2-74), varied from 31°F to 41°F in Box 1 and from 33°F to 45°F in Box 2. Daily average temperature fluctuation (range) was about 7°F in both boxes.

The test period during which the data of Table 1 were obtained included regular regeneration periods during which the internal box temperature was maintained by the stabilizer. Thus, it is evident that, under these conditions the Icy Ball Unit in a 4 cu ft insulated storage box is a stable refrigeration source.

Table 2 represents a sample data sheet showing mainly the internal pressure history of the Icy Ball system during regeneration (heating the hot ball). The Table shows that at zero time (the start of a 90-minute regeneration phase), the internal pressure was 15 psig. The pressure rose steadily with heating until at 90 minutes it was 140 psig. The Table also shows the rapid pressure drop that occurred within the first 10 minutes of the refrigeration phase, with a rise in cooling water temperature of only a few degrees.

Field Tests

Meteorological data taken during 16 days of continuous field tests in the Panama Canal Zone show the ambient temperature range was 66°F to 90°F and the relative humidity varied from 47% to 96% (Table 3). The field test results are summarized in Table 4 and they show that the Icy Ball Unit in a 4 cu ft box under these ambient conditions maintained an average inside-the-box temperature of 43°F (std. dev. 2.9°). This meets the major performance requirement for the present stage of development. In an 8 cu ft box, however, the present Icy Ball Unit did not maintain an average inside-the-box temperature low enough to preserve food and medical supplies. As shown in Table 4, the average temperature in an 8 cu ft box was 62.5°F (std. dev. 5.5°F).

TABLE 1

AVERAGE DAILY TEMPERATURES IN 4 CU FT BOXES WITH ICY BALL TEST UNITS
UNDER LABORATORY CONDITIONS

<u>BOX #</u>	<u>DATE</u>	<u>TEMPERATURE, °F</u>	
		<u>Average</u>	<u>Range/Day</u>
Box 1	2-2-74	Start 67.5	
Box 2	2-2-74	Start 68.0	
1	2-3-74	35	30-40
2	2-3-74	41	33-49
1	2-4-74	31	28-34
2	2-4-74	33	28-38
1	2-5-74	35	31-39
2	2-5-74	37	35-39
1	2-6-74	38	35-41
2	2-6-74	44	41-47
1	2-7-74	33	30-36
2	2-7-74	41	38-44
1	2-8-74	32	30-34
2	2-8-74	35	33-37
1	2-9-74	31	28-34
2	2-9-74	41	39-43
1	2-10-74	38	36-40
2	2-10-74	41	37-45
1	2-11-74	41	39-44
2	2-11-74	45	39-50
1	2-12-74	35	32-38
2	2-12-74	41	38-44
1	2-13-74	33	30-36
2	2-13-74	45	41-49
1	2-14-74	Not recorded	
2	2-14-74	Not recorded	

TECHNICAL LIBRARY
 BLDG. 305
 ABERDEEN PROVING GROUND, MD.
 STEAP-TL

TABLE 1 (Cont'd)

<u>BOX #</u>	<u>DATE</u>	<u>TEMPERATURE, °F</u>	
		<u>Average</u>	<u>Range/Day</u>
1	2-15-74	Not recorded	
2	2-15-74	Not recorded	
1	2-16-74	35	32-38
2	2-16-74	43	38-48
1	2-17-74	35	30-40
2	2-17-74	37	33-41
1	2-18-74	36	32-40
2	2-18-74	38	36-40
1	2-19-74	Not recorded	
2	2-19-74	Not recorded	
1	2-20-74	35	33-37
2	2-20-74	37	35-39
1	2-21-74	34	30-38
2	2-21-74	39	33-45
1	2-22-74	35	31-39
2	2-22-74	41	38-44
1	2-23-74	33	30-36
2	2-23-74	40	38-42
1	2-24-74	31	27-35
2	2-24-74	35	32-38
1	2-25-74	35	32-37
2	2-25-74	38	34-42
1	2-26-74	35	31-39
2	2-26-74	39	35-43
1	2-27-74	35	33-37
2	2-27-74	37	33-41
1	2-28-74	35	30-40
2	2-28-74	40	38-42

TABLE 2

ICY BALL REGENERATION DATA UNDER LABORATORY CONDITIONS

<u>TIME (Min)</u>	<u>CONDITION</u>	<u>PRESSURE (psig)</u>	<u>COOLING WATER TEMPERATURE (°F)</u>
0	On Burner	15	--
+5	"	20	--
10	"	30	--
15	"	40	--
30	"	45	--
45	"	70	--
60	"	120	--
75	"	130	--
90	"	140	--
0	Off Burner/ in Water*	100	68
+5	In Water	60	74
10	"**	40	74

*Start of refrigeration phase.

**Removed from cooling water after ten minutes.

TABLE 3

MET DATA FROM CHIVA-CHIVA ANTENNA FARM (Open)
December 1973

DATE	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
TEMP. HIGH (°F)	88	87	88	88	88	86	86	88	87	87	88	86	87	90	85	86	86
TEMP. LOW (°F)	70	73	70	70	69	70	71	72	73	72	66	70	69	73	73	70	74
R. H. HIGH (%)	96	93	92	88	87	95	92	86	84	94	86	89	96	92	92	92	95
R. H. LOW (%)	53	53	48	48	54	67	61	54	48	49	53	53	55	47	56	54	71
RAIN- FALL (In.)	0	0	.07	0	0	0.70	1.25	0.45	.58	0	0	0.02	0	0	0	0	0

NOTE: Temperature and humidity are recorded by a hygrothermograph located under a standard meteorological shelter. Accuracy is $\pm 5\%$.

TABLE 4

TEMPERATURE INSIDE BOXES IN FIELD TESTS
(Recorded at approximately 24 hr intervals)

<u>Date</u>	<u>8 Cu Ft Box</u>	<u>4 Cu Ft Box</u>
4 Dec*	85°F	85°F
5 Dec	70°F	62°F
6 Dec**	65°F	38°F
7 Dec	57°F	40°F
8 Dec	58°F	40°F
9 Dec	58°F	40°F
10 Dec	60°F	42°F
11 Dec	60°F	42°F
12 Dec	76°F One gal anti-freeze put in stabilizer	42°F
13 Dec	70°F	44°F
14 Dec	65°F	44°F
15 Dec	62°F	49°F
16 Dec	55°F	44°F
17 Dec	59°F	45°F
18 Dec	65°F	45°F
19 Dec	66°F	46°F
20 Dec	63°F Testing stopped	46°F Testing stopped
<hr/>		
Average***	62.5°F	43°F
Standard deviation	5.5°F	2.9°F
<hr/>		

*Start-up

**Temperatures considered stabilized at 48 hrs

***From 6 Dec to 20 Dec

DISCUSSION

Performance of the Icy Ball Refrigerator in a 4 cu ft storage box under both laboratory conditions and hot-wet field conditions proved to be reliable. In laboratory tests a total of 52 regenerations was performed with no failures. This degree of reliability is a function of the pressure reached during regeneration. The maximum average pressure attained during regeneration in these tests was 150 psig, which is well below the pressure at which water begins to transfer to the cold ball. With the concentration of ammonia in water used in these units, steam begins to start generating and to transfer to the cold ball at approximately 175 psig.

Another favorable characteristic of these units was the rapid formation of ice on the cold ball during the 10-minute cooling of the hot ball. Ice started forming on the cold ball during the last 2 minutes of cooling, which is indicative of rapid heat transfer between the cooling water and the hot ball. The temperature of the cooling water was about 65°F. If warmer water had been used, formation of ice on the cold ball, however, may not have occurred until the pressure in the unit fell below 40 psig.

In each unit the cold ball was nearly empty after 24 hours of refrigeration, which is another indication of efficient ammonia transfer. In both the laboratory and field tests the present Icy Ball Units maintained a lower temperature in the 4 cu ft boxes than had been obtained with the earlier units fabricated under this program. The reason for this is probably that a small ratio of ammonia-to-water was used in the present units. If a larger volume of ammonia-water mixture in the same ratio were to be used, it is quite possible that a suitably low temperature (45°F) could be maintained in a 4 cu ft box under hot-wet ambient conditions for as long as 36 hours with a 90-minute regeneration time.

CONCLUSION

The Icy Ball Refrigerator developed under the present contract is a reliable system and can maintain temperatures averaging 43°F ($\delta=2.9^{\circ}\text{F}$) in a 4 cu ft insulated box for a period of 24 hours under hot-wet ambient conditions.

RECOMMENDATIONS

1. Tests should be performed with the Icy Ball Units to determine their performance characteristics as a function of at least 4 specified levels of ambient temperature/relative humidity.
2. The maximum regenerating pressure in the Icy Ball system that should be permitted under operating conditions should be kept significantly below 175 psig, the pressure at which water vapor will transfer to the cold ball.

DISTRIBUTION LIST

	<u>Copies</u>
Commander US Army Materiel Command ATTN: AMCDL 5001 Eisenhower Avenue Alexandria, VA 22333	1
Commander US Army Materiel Command ATTN: AMCRD 5001 Eisenhower Avenue Alexandria, VA 22333	3
Commander US Army Materiel Command ATTN: AMCRD-P 5001 Eisenhower Avenue Alexandria, VA 22333	1
Director of Defense, Research & Engineering Department of Defense WASH DC 20301	1
Director Defense Advanced Research Projects Agency WASH DC 20301	3
HQDA (DARD-DDC) WASH DC 20310	4
HQDA (DARD-ARZ-C) WASH DC 20310	1
HQDA (DAFD-ZB) WASH DC 20310	1
HQDA (DAMO-PLW) WASH DC 20310	1
Commander US Army Training & Doctrine Command ATTN: ATCD Fort Monroe, VA 23651	1

Commander US Army Combined Arms Combat Developments Activity (PROV) Fort Leavenworth, KS 66027	1
Commander US Army Logistics Center Fort Lee, VA 23801	1
Commander US Army CDC Intelligence & Control Systems Group Fort Belvoir, VA 22060	1
TRADOC Liaison Office HQS USATECOM Aberdeen Proving Ground, MD 21005	1
Commander US Army Test and Evaluation Command Aberdeen Proving Ground, MD 21005	1
Commander US Army John F. Kennedy Center for Military Assistance Fort Bragg, NC 28307	1
Commander-In-Chief US Army Pacific ATTN: GPOP-FD APO San Francisco 96558	1
Commander Eighth US Army ATTN: EAGO-P APO San Francisco 96301	1
Commander Eighth US Army ATTN: EAGO-FD APO San Francisco 96301	1
Commander-In-Chief US Army Europe ATTN: AEAGC-ND APO New York 09403	4
Commander US Army Alaska ATTN: ARACD APO Seattle 98749	1

Commander MASSTER ATTN: Combat Service Support & Special Programs Directorate Fort Hood, TX 76544	1
Commander US MAC-T & JUSMAG-T ATTN: MACTRD APO San Francisco 96346	2
Senior Standardization Representative US Army Standardization Group, Australia c/o American Embassy APO San Francisco 96404	1
Senior Standardization Representative US Army Standardization Group, UK Box 65 FPO New York 09510	1
Senior Standardization Representative US Army Standardization Group, Canada Canadian Forces Headquarters Ottawa, Canada K1A0K2	1
Director Air University Library ATTN: AUL3T-64-572 Maxwell Air Force Base, AL 36112	1
Battelle Memorial Institute Tactical Technical Center Columbus Laboratories 505 King Avenue Columbus, OH 43201	1
Defense Documentation Center (ASTIA) Cameron Station Alexandria, VA 22314	12
Commander Aberdeen Proving Ground ATTN: STEAP-TL Aberdeen Proving Ground, MD 21005	2
Commander US Army Edgewood Arsenal ATTN: SMUEA-TS-L Aberdeen Proving Ground, MD 21010	1

US Marine Corps Liaison Officer
Aberdeen Proving Ground, MD 21005

1

Director
Night Vision Laboratory
US Army Electronics Command
ATTN: AMSEL-NV-D (Mr. Goldberg)
Fort Belvoir, VA 22060

1

Commander
US Air Force Special Communications Center (USAFSS)
ATTN: SUR
San Antonio, TX 78243

1

Commander
US Army Armament Command
ATTN: AMSAR-ASF
Rock Island, IL 61201

1